

## Kesä2025



Oil Pattern Distance Forward Oil Total Tank Configuration 44 10.85 mL A Only Reverse Brush Drop Reverse Oil Total Tank A Conditioner 42 8.65 mL K Current Oil Per Board Volume Oil Total Tank B Conditioner 50 ul 19.5 mL K Current

	START	STOP	LOADS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	18	3	74	0.0	2.5	2.5	3700
2	9L	9R	2	18	3	46	2.5	7.6	5.1	2300
3	10L	10R	3	18	3	63	7.6	15.2	7.6	3150
4	12L	12R	2	18	3	34	15.2	20.3	5.1	1700
5	2L	2R	0	18	3	0	20.3	28.0	7.7	0
6	2L	2R	0	22	3	0	28.0	44.0	16.0	0

	START	STOP	LOADS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL	_
1	2L	2R	0	26	3	0	44.0	35.0	-9.0	0	
2	14L	14R	3	22	3	39	35.0	25.7	-9.3	1950	
3	13L	13R	3	18	3	45	25.7	18.1	-7.6	2250	
4	12L	12R	3	14	3	51	18.1	12.2	-5.9	2550	
5	11L	11R	2	14	3	38	12.2	8.3	-3.9	1900	
6	2L	2R	0	14	3	0	8.3	0.0	-8.3	0	

Cleaner Ratio Main Mix 33:1 Forward
Cleaner Ratio Back End Mix 19:1 Reverse
Cleaner Ratio Back End Distance 59 Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	MIddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	10	2,78	1.03	1,03	2,78	10



